

Pagel Spezial- Beton GmbH & Co. KG

EH 130 - Hardener

1. Identification of substance/preparation and of the company/undertaking

Trade name : EH 130 - Hardener
Application of the substance / the preparation : Epoxi-coating
Hardening agnt / Curing agent
Company : Pagel Spezial Beton GmbH & Co. KG
Wolfsbankring 9
D-45355 Essen
Phone number : ++49 (0)201 / 68504 0
Emergency phone : Toxic information headquarter Berlin
++49 (0)30 / 19 240

2. Composition/Information on ingredients

Chemical characterization :
Description : Mixture of the substances listed below with harmless additions.
Dangerous components :

Chemical Name	CAS-No.	Symbol(s)	R-phrase(s)	Concentration
benzyl alcohol EC-No.: 202-859-9	100-51-6	,Xn,	R20/22	25-50%
isophorone diamine EC-No. : 220-666-8	2855-13-2	,C,	R21/22-34-43-52/53	25-50%
m-xylylenediamine EG-Nr. : 216-032-5	1477-55-0	,C,	R20/22-34-43-52/53	5-15%

Additional information

For the wording of the listed risk phrases refer to section 16.

3. Hazards identification

Hazard designation:

C Corrosive

Information pertaining to particular dangers for man and environment

Harmful if inhaled, if swallowed and by skin contact.
Causes burns.
May cause sensitization by inhalation and skin contact.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Classification system:

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

EH 130 - Hardener

4. First aid measures

- General information : Seek immediate medical advice.
Instantly remove any clothing soiled by the product.
Take affected persons into the open air.
- After eye contact : Rinse opened eye for several minutes under running water.
Call a doctor immediately.
- After skin contact : Instantly wash with water and soap and rinse thoroughly.
- After inhalation : Supply fresh air and call for doctor for safety reasons.
- After swallowing : Drink copious amounts of water and provide fresh air.
Instantly call for doctor.
-

5. Fire fighting measures

- Suitable extinguishing agents : Use fire fighting measures that suit the environment.
- Special hazards caused by the material, its products of combustions or flue gases : Can be released in case of fire
Carbon monoxide (CO)
Nitrogen oxides (NOx)
- Protective equipment : Put on breathing apparatus.
-

6. Accidental release measures

- Personal-related safety precautions : Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection : Prevent material from reaching sewage system, holes and cellars.
- Measures for cleaning/collecting : Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose of contaminated material as waste according to item 13.
Ensure adequate ventilation.
-

7. Handling and storage

Handling:

- Information for safe handling : Open and handle container with care.
Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires : Keep ignition sources away - Do not smoke.

Storage:

- Requirements to be met by storerooms and containers : No special requirements.
- Information about storage in one common storage facility : Not required.
- Further information about storage conditions : Store in a cool place.. Heat will increase pressure and may lead to the container exploding.

8. Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Control parameters	Update	Basis
m-xylylenediamine	1477-55-0	0.1 mg/m ³		

Additional information about design of technical systems : No further data; see item 7.

Components with critical values that require monitoring at the workplace:

The product does not contain any relevant quantise of materials with cirtical values that have to be monitored at the workplace.

Personal protective equipment:

- General protective and hygienic measures : Keep away from foodstuffs, beverades and food. Instantly remove any soiled and impregnated garments.
Wash hands during braeks and at the end of the work.
Avoid contact with the eyes and skin.
- Breathing equipment : Not necessary if room is well-ventilated.Only during spraying without adequate removal by suction.
Self-contained breathing apparatus.
- Eye protection : Tightly fitting safety glasses. Gauze goggles.
- Body protection : Protective work clothing.
Apron.
Boots.
- Protection of hands : Use gloves of stable material (e.g. Nitrile) – if necessary tricoted to improve the wearability.
- Material of gloves : Nitrile rubber, NBR
Buthyl rubber, BR
- Penetration time of glove material : The exact braek trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

9. Physical and chemical properties

- Physical state : liquid
- Colour : yellow
- Odour : amine-like
- Thermal decomposition : > 250 °C
- Boiling point : > 200 °C
- Self-inflammability : Product is not selfigniting.
- Danger of explosion : Product is not explosive.
- Flash point : approx. 130 °C method: DIN 51758
- Density : approx. 1,00 g/cm³ at (20 °C) method: DIN 51757
- Solubility in / Miscibility with water : Not miscible or difficult to mix.

EH 130 - Hardener

Viscosity : approx. 200-300 mPas at 25°C

10. Stability and reactivity

Thermal decomposition / conditions to be avoided : No decomposition if used according to specifications.

Dangerous reactions : No dangerous reactions known

Dangerous products of composition : No dangerous decomposition products known.

11. Toxicological information

Acute toxicity	LD/LC50 values that are relevant for classification:		
	2855-13-2 isophorone diamine		
	Oral	LD50	250 mg/kg (rat)
			Oral Dermal
	1477-55-0 m-Xylylendiamin		
	Oral Dermal Inhalativ	LD50 LD50 LC50/4 h	1040 mg/kg (rat) 2000 mg/kg (rab) 2,4 mg/l (rat)
			Oral Dermal
	100-51-6 benzyl alcohol		
	Oral Dermal	LD50 LD50	1230 mg/kg (rat) 2000 mg/kg (rbt)
<i>Primary irritant effect:</i>	on the eye: Strong caustic effect. on the skin: Caustic effect on skin and mucous membranes. Sensitization Sensitization possible by skin contact.		
<i>Additional toxicological information</i>	The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version: Harmful Corrosive Irritant Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.		

12. Ecological information

General notes : Do not allow product to reach ground water, water bodies or sewage system.

13. Disposal considerations

Product:

Pagel Spezial- Beton GmbH & Co. KG

EH 130 - Hardener

Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 00 00: WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01 00: wastes from MFSU and removal of paint and varnish

08 01 11: waste paint and varnish containing organic solvents or other dangerous substances

Uncleaned packagings:**Recommendation:**

Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.

14. Transport information**Road transport** :

ADR/RID

UN-No: : 2735

Class : 8 Corrosive substances

Classification code : C7

Packaging group : III

Risk No. : 80

ADR/RID- Labels : 8

Proper shipping name : AMINES , LIQUID, CORROSIVE, N.O.S.
(isophorone diamine)**Sea transport** :

IMDG :

UN-No: : 2735

Class : 8

Packaging group : III

ADR/RID- Labels : 8

MFAG :

EmS : F-A-S-B

Proper shipping name : AMINES , LIQUID, CORROSIVE, N.O.S.
(isophorone diamine)**Air transport**

IATA-DGR:

UN/ID No. : UN 2735

Class : 8

Packaging group : III

Packing instruction : 820
(cargo aircraft)

Pagel Spezial- Beton GmbH & Co. KG

EH 130 - Hardener

Max. Qty/Pack. : 60.00L
(999.00=No limit)

Packing instruction : 818
(passenger aircraft)

ADR/RID- Labels : 8

Proper shipping name : AMINES , LIQUID, CORROSIVE, N.O.S.
(isophorone diamine)

15. Regulatory information

Designation according to EC guidelines:

The product has been labelled in accordance with EC Directives / relevant national laws.

Code letter and hazard designation of product :



C Corrosive

R-Phrases : R20/21/22: Harmful if inhaled, if swallowed and by skin contact.
R34: Causes burns
R43: May cause sensitization by skin contact.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-Phrases : S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.
S45: In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).

Hazardous – determining components of labelling : isophorone diamine
benzyl alcohol

16. Other information**List of R-phrases (section 2)**

20/22 Harmful by inhalation and if swallowed
21/22 Harmful in contact with skin and if swallowed
34 Causes burns
43 May cause sensitization by skin contact
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Department issuing data specification sheet: Technic

Contact: laboratory

All information is based on results gained from experience and tests and is believed to be accurate but is given without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry out sufficient tests to establish the suitability of any products for their intended applications.