



PAGEL[®]
SPEZIAL-BETON GMBH & CO KG



DECLARATION OF PERFORMANCE
according Annex III of the Regulation (EU) No 305/2011

Name of the product R34 PAGEL Flex Adhesive

No. 280203

1. Unique identification code of the product-type:
EN 12004 C2
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
batch number: see packaging of the product
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Improved cementitious adhesive for internal and external tiling
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
PAGEL SPEZIAL-BETON GMBH & CO. KG
Wolfsbankring 9
45355 Essen, Germany
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
not relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
System 4 (for reaction-to-fire regulations)
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
The notified testing laboratory Materialprüfungsamt Nordrhein-Westfalen, identification number 0432, performed the determination of the product-type on the basis of type testing under system 3 and issued: test report 220002756-03
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
not relevant



9. Declared performance

Essential characteristic	Performance	Harmonised technical specification
Reaction to fire ¹	E	EN 12004:2007+A1:2012
Bond strength as		
Initial tensile adhesion strength	≥ 1,0 N/mm ²	
Durability of bond strength as:		
Tensile adhesion strength after water immersion	≥ 1,0 N/mm ²	
Tensile adhesion strength after heat ageing	≥ 1,0 N/mm ²	
Tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm ²	
Release of dangerous substances	NPD	

¹ Reaction to fire after CWFT from 09.02.2010.

NPD "No Performance Determined"

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Daniel Schempershofe, Head of Laboratory
(name and function)

Essen, 01.07.2013
(place and date of issue)


.....
(signature)