



**PAGEL**<sup>®</sup>  
SPEZIAL-BETON GMBH & CO KG



DECLARATION OF PERFORMANCE  
according Annex III of the Regulation (EU) No 305/2011

**EH115 PAGEL-EPOXI-RESIN**  
Resin primer

No. 510300

1. Unique identification code of the product-type:  
EN 13813: SR – B1,5
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):  
batch number: see packaging of the product
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
EN 13813  
Synthetic resin for internal uses
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):  
PAGEL Spezial-Beton GmbH & Co.KG  
Wolfsbankring 9  
D-45355 Essen
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):  
not relevant
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:  
System 4 (for internal uses)
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:  
not relevant
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
not relevant



9. Declared performance

| Essential characteristic        | Performance                   | Harmonised technical specification |
|---------------------------------|-------------------------------|------------------------------------|
| Reaction to fire                | E <sub>fi</sub> <sup>a)</sup> | EN 13813:2002                      |
| Release of corrosive substances | SR                            |                                    |
| Water permeability              | NPD                           |                                    |
| Wear resistance                 | NPD                           |                                    |
| Bond strength                   | ≥ B1,5                        |                                    |
| Impact resistance               | NPD                           |                                    |
| Sound insulation                | NPD                           |                                    |
| Sound absorption                | NPD                           |                                    |
| Thermal resistance              | NPD                           |                                    |
| Chemical resistance             | NPD                           |                                    |
| Dangerous substances            | NPD                           |                                    |

a) According to Commission Decision 2010/85/EU of 9 February 2010 the product fulfils the reaction-to-fire performance class E/E<sub>fi</sub> without further testing  
NPD "No Performance Determined"

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dipl. Ing. Bernd Gehrke  
Technical Management

D-Essen, 19.06.2013

.....  
(signature)