

CLEANER AND THINNER

EH CLEANER AND THINNER

TEST CERTIFICATES AND SUPPORTING DOCUMENTS

- › Company certification acc. to DIN EN ISO 9001:2015

PROPERTIES

- › Special cleaner for all kind of contaminated floors
- › Thinner for paints, lacquers, resins, etc.
- › Water-dilutable
- › Non-volatile
- › For easily and efficiently cleaning tools after work
- › For easily and efficiently removing hardened materials from tools

AREAS OF APPLICATION

- › Cleaning contaminated industrial floors
- › Cleaning tools
- › Removing oils and grease
- › Will remove paint and coatings when used in concentrated form

TECHNICAL DATA

TYPE		EH CLEANER
Colour		colourless
Odor		mild amine-like
Form		liquid
Minimum processing temperature	°C	≥ 0
Flash point	°C	91
Ignition temperature	°C	245
Vapour pressure (20 °C)	mbar	0.29
Miscibility with water		complete

Delivery form: 8-L canister

Storage time: Unlimited. Cool, dry, free from frost.
Unopened in its original container.

Storage: Dry, free from frost

Hazard category: Hazard class:
Observe safety data sheet

PROCESSING

AREAS OF APPLICATION:

EH CLEANER AND THINNER can - depending on conditions - be applied with a brush, roller or cloth. Allow to take effect for some time after application (depending on the specific requirements, this can be up to 24 hours).

Finally clean the cleaned areas thoroughly with water so that no residues remain.